



MOMENTIVE
performance materials

SilGlaze* II SCS2811-D1

silicone backbedding sealant

Product Description

SilGlaze II SCS2811-D1 silicone backbedding sealant is a one-part, neutral, very fast cure, high modulus silicone sealant that develops significant green strength in the early cure hours. SilGlaze II SCS2811-D1 silicone backbedding sealant may be an excellent candidate for use as a bedding seal in the construction of residential and commercial doors and windows.

Typical Performance Properties

- **Silicone Durability** - Cured silicone rubber exhibits excellent long-term resistance to natural weathering, including: ultraviolet radiation, high and low temperatures and rain and snow, with negligible change in elasticity.
- **Primerless Adhesion** - May be considered a candidate for use with numerous construction-related materials, including: glass, polycarbonate, vinyl, numerous plastics, treated and untreated wood, fluoropolymer and powder coated paints, and other coated aluminum finishes. Some finishes or substrates may require a primer.
- **Fast Green Strength** - Proprietary patented technology develops green strength in the first 24 hours faster than most other single-component fenestration sealants. SCS2811-D1 sealant can attain 18-20 psi in 5 hours and up to 40-50 psi after 24 hours in some designs.
- **±25% Movement Capacity** - Can accommodate 25% movement in both extension and compression.
- **Standard Equipment** - SilGlaze II SCS2811-D1 sealant is easily dispensed using common pumping equipment. Heating of this product is not necessary.
- **Excellent Processability** - The low pumping viscosity and high application rate of SilGlaze II SCS2811-D1 sealant provides for longer pump life with reduced maintenance on equipment and faster with easier tooling effort.
- **Easy Repairs** - The traditional silicone rubber properties of SilGlaze II SCS2811-D1 sealant allows for frames or components to be easily deglazed as would be expected from silicone materials.
- **Product Chemistry** - Neutral cure.

Momentive Performance Materials is an exclusive licensee of General Electric. Momentive Performance Materials provides versatile materials as the starting point for its creative approach to ideas that help enable new developments across hundreds of industrial and consumer applications.

We are helping customers solve product, process, and performance problems; our silanes, fluids, elastomers, sealants, resins, adhesives, urethane additives, and other specialty products are delivering innovation in everything from car engines to biomedical

devices. From helping to develop safer tires and keeping electronics cooler, to improving the feel of lipstick and ensuring the reliability of adhesives, our technologies and enabling solutions are at the frontline of innovation.



Exclusive
Licensee

SilGlaze* II SCS2811-D1 silicone backbedding sealant

Basic Uses

- SilGlaze II SCS2811-D1 sealant may be used for in-shop window fabrication as a bedding bead or for cap, toe, heel head applications and for general purpose sealing.

Limitations

SilGlaze II SCS2811-D1 sealant is not recommended:

- For use underwater or in other applications where the product will be in continuous contact with water.
- For use in food contact applications.
- When painting of the cured sealant is desired (unless appropriate specialized paint products are used).
- For adhesion on bare metals or surfaces subject to corrosion (*i.e.*, mill aluminum, bare steel, etc.).

SilGlaze II SCS2811-D1 sealant should not be applied or used:

- In structural glazing applications.
- On wet, damp, frozen or contaminated surfaces.
- In cavities or designs where the cure depth exceeds 1/2".

Precautions

- This material requires atmospheric moisture to cure from paste to rubber and may not attain its listed final cured rubber properties when used in designs or applications where the silicone is encapsulated and without access to atmospheric moisture.
- Maximum cure depth from an air interface should not exceed 3/8". When used in colder less humid environments, cure depth should not exceed 1/4" from an air interface.
- When used in glass-to-glass butt joints, use caution to completely fill the joint as air pockets or bubbles can become entrapped in the sealant which may be visible through the sealant.
- May stress craze polycarbonate in some applications.

Packaging

SilGlaze II SCS2811-D1 sealant is available in 5 gallon pails containing 40.0 lbs. /18.1 kg or 55 gallon fiber drums containing 450.0 lbs. / 204.1 kg with a polyethylene bag liner.

Colors

SilGlaze II SCS2811-D1 sealant is translucent.

Technical Services

Additional technical information and literature may be available from Momentive Performance Materials.¹ Laboratory facilities and application testing are available upon request from Momentive Performance Materials.¹ Any technical advice furnished by Momentive Performance Materials¹ or any representative of GE sealant concerning any use or application of any sealant is believed to be reliable but Momentive Performance Materials¹ makes no warranty, express or implied, of suitability for use in any application for which such advice is furnished.

Applicable Standards

SilGlaze II SCS2811-D1 sealant meets or exceeds the requirements of the following standards and/or specifications:

American Society for Testing & Materials International

- ASTM C920 Standard Specification for Elastomeric Joint Sealants; Type S, Grade NS, Class 25, Use A, G, O

U.S. Federal Specifications:

(Widely referenced but cancelled Sept. 1996)

- TT-S-001543A Sealing Compound: Silicone Rubber Base (for Caulking, Sealing & Glazing in Buildings and Other Structures)
- TT-S-00230C Sealing Compound: Elastomeric Type, Single Component (for Caulking, Sealing & Glazing in Buildings and Other Structures)

American Architectural Manufacturers Association

- AAMA 802.3-92 Back Bedding Glazing Compound, Type 1
- AAMA 802.3-92 Back Bedding Glazing Compound, Type 2
- AAMA 805.2-92 Back Bedding Glazing Compound, Group C
- AAMA 808.3-92 Exterior Perimeter Sealing Compound

SilGlaze* II SCS2811-D1 silicone backbedding sealant

Specifications

Typical property values of SilGlaze II SCS2811-D1 sealant as supplied and cured are set forth in the tables below. Typical product data values should not be used as specifications.

Typical Properties – Supplied

Property	Value ⁽¹⁾	Test Method
Consistency	Paste	
Polymer	100% silicone	
VOC	<34 g/l	WPSTM C1454
Work Life (tooling time)	5-10 minutes	
Tack Free Time	15 minutes (@ 72°F, 50% RH)	ASTM C679
Sag/Slump	0.1" max.	ASTM D2202

Typical Properties – Cured

(after cure of 21 Days at 23°C (73°F) & 50% Relative Humidity)

Property	Value ⁽¹⁾	Test Method
Hardness, Durometer (Type A Indentor)	24	ASTM D2240
Ultimate Tensile Strength	284 psi (1.95 MPa)	ASTM D412
Ultimate Elongation	415%	ASTM D412
Peel Strength (average) (21-day cure @ 75°F (21°C) 50% RH)	34 pli	ASTM C794
Joint Movement Capability	±25%	ASTM C719
Service Temperature Range (after cure)	-55°F to +300°F (-48°C to 149°C)	
Weathering and U.V. Resistance	Excellent	GE 20 yr. study
Cure Time (1/4" or 6 mm deep section) @ 75°F (24°C) 50% RH	<24 hours	
Full Cure (most common bead sizes)	3-4 days	

(1) Average value. Actual value may vary.

Installation

IN ALL APPLICATIONS IT IS IMPORTANT TO CONFIRM THE ACCEPTIBILITY OF EACH SEALANT-SUBSTRATE COMBINATION WITH AN ADHESION TEST PRIOR TO PROCEEDING WITH USE.

Surface Preparation

SilGlaze II SCS2811-D1 sealant has been formulated to develop adhesion to most materials commonly used in the manufacturing of commercial glazing constructions including: glass, vinyl extrusions, fluoropolymer, acrylic, and polyester paints, powder coated aluminum, and numerous plastic materials. Sealants may not adhere to these substrates or less than optimal adhesion may result if the surface is contaminated. Foreign materials such as, but not limited to, dirt, dust, oils and water and other contaminants particular to certain substrates including machine oils, water repellants, lubricants, waxes on painted surfaces, salt deposition on anodized surfaces can and may interfere with development of adhesion.

Momentive Performance Materials¹ can provide, upon request, laboratory testing services to evaluate the adhesion and compatibility of its sealants to submitted substrates. This testing can provide information on adhesive bonding quality to individual substrates and direction to the user on how adhesion may be improved through modification of the substrate surface properties by special cleaning and/or priming procedures. Momentive Performance Materials¹ can also provide upon request technical information including specific cleaning procedures and priming recommendations for the customer to evaluate. Momentive Performance Materials¹ does not provide joint design services.

Users of this material are strongly advised to conduct their own testing to determine if the adhesion to the desired substrate is satisfactory for their needs. It is also recommended that the user conduct periodic quality control testing on their substrates and sealant during the course of using them in manufacturing operations to maintain a continued assurance that substrate, sealant or other conditions that could affect adhesion have not changed and that adhesion requirements are being met.

SilGlaze* II SCS2811-D1 silicone backbedding sealant

Installation (continued)

Sealant Application

- Begin by installing backup material for joint or joint filler, setting blocks, spacer shims and tapes as needed.
- In a continuous operation, apply SilGlaze II SCS2811-D1 sealant horizontally in one direction and vertically from the bottom to the top of the joint opening.
- Apply the sealant with a positive pressure by pushing the bead ahead of the nozzle and making sure that the entire cavity is filled sans air pockets or voids.
- Tooling should be done neatly, forcing the sealant into contact with the sides of the joint or cavity, thus helping to eliminate any internal voids and assuring good substrate contact.
- Due to the smooth consistency of SilGlaze II SCS2811-D1 sealant tooling agents such as water, soap or detergent solutions are not necessary or recommended. Dry tooling is recommended.
- For cap bead glazing the sealant applied to the sill should be tooled in such a fashion to prevent pooling of precipitation and cleaning solution.
- Sealant should only be applied to surfaces that are clean, dry and free of frost.

Cleaning of Excess Sealant

- For glass, metal, and plastic surfaces uncured excess material can be removed using a solvent. Use care when using solvents on plastic materials as some solvents can soften some plastics.
- For glass, metal, and plastic surfaces cured excess material can be removed using a blade by scraping or cutting.
- If excess material unintentionally contacts the surfaces of porous materials, the sealant is best allowed to progress through the initial cure or set-up and then mechanically removed by abrasion or other suitable means.

Method of Application

SilGlaze II SCS2811-D1 sealant is easily dispensed directly from pails and drums with standard single component pumping equipment.

Patent Status

Nothing contained herein shall be construed to imply the nonexistence of any relevant patents or to constitute the permission, inducement or recommendation to practice any invention covered by any patent, without authority from the owner of the patent.

Technical subject matter in this publication is described and protected by one or more pending US patent applications and foreign counterparts.

Product Safety, Handling and Storage

Customers considering the use of this product should review the latest Material Safety Data Sheet and label for product safety information, handling instructions, personal protective equipment if necessary, and any special storage conditions required. Material Safety Data Sheets are available at www.momentive.com or, upon request, from any Momentive Performance Materials¹ representative. Use of other materials in conjunction with Momentive Performance Materials¹ products (for example, primers) may require additional precautions. Please review and follow the safety information provided by the manufacturer of such other materials.

SilGlaze* II SCS2811-D1 silicone backbedding sealant

Emergency Service

Momentive Performance Materials¹ maintains an around-the-clock emergency service for its products. The American Chemistry Council (CHEMTREC), Transport Canada (CANUTEC), and the Chemical Emergency Agency Service also maintain an around-the-clock emergency service for all chemical products:

Location	GE Branded Products	All Chemical Products
Mainland U.S., Puerto Rico	518.233.2500	CHEMTREC: 800.424.9300
Alaska, Hawaii	518.233.2500	CHEMTREC: 800.424.9300
Canada	518.233.2500	CANUTEC: 613.996.6666 (collect) or CHEMTREC: 800.424.9300
Europe, Middle East, Africa	+32.(0)14.58.45.45 (Belgium)	CHEMTREC: +1-703.527.3887 (collect)
Latin America, Asia/Pacific, all other locations worldwide	+518.233.2500	CHEMTREC: +1-703.527.3887 (collect)
At sea	Radio U.S. Coast Guard, which can directly contact Momentive Performance Materials ¹ at 518.233.2500	CHEMTREC: 800.424.9300

DO NOT WAIT. Phone if in doubt. You will be referred to a specialist for advice.

CUSTOMER SERVICE CENTERS

North America

E cs-na.silicones@momentive.com

- | | | |
|---|--------------------------|--------------------------|
| • Specialty Fluids | T +1.800.523.5862 | F +1.304.746.1654 |
| • UA, Silanes and Specialty Coatings | T +1.800.334.4674 | F +1.304.746.1623 |
| • RTV's and Elastomers | T +1.800.332.3390 | F +1.304.746.1623 |
| • Consumer Sealants & Construction Sealants and Adhesives | T +1.877.943.7325 | F +1.304.746.1654 |
-

Latin America

E cs-la.silicones@momentive.com

- | | | |
|--|---------------------------|---------------------------|
| • Argentina & Chile | T +54.11.4862.9544 | F +54.11.4862.9544 |
| • Brazil | T +55.11.4534.9650 | F +55.11.4534.9660 |
| • Mexico & Central America | T +52.55.5899.5135 | F +52.55.5899.5138 |
| • Venezuela, Ecuador, Peru
Colombia & Caribbean | T +58.212.285.2149 | F +58.212.285.2149 |
-

Europe, Middle East, Africa and India

E cs-eur.silicones@momentive.com

T +00.800.4321.1000
T +31.164.225350

Pacific

E cs-ap.silicones@momentive.com

T +1.800.820.0202 **F** +81.276.31.6259
T +0.81.276.20.6182

Worldwide Hotline

T +1.607.786.8131 **F** +1.607.786.8309
T +1.800.295.2392

Visit us at Momentive.com

THE MATERIALS, PRODUCTS AND SERVICES OF MOMENTIVE PERFORMANCE MATERIALS INC., MOMENTIVE PERFORMANCE MATERIALS USA INC., MOMENTIVE PERFORMANCE MATERIALS ASIA PACIFIC PTE. LTD., MOMENTIVE PERFORMANCE MATERIALS WORLDWIDE INC., MOMENTIVE PERFORMANCE MATERIALS GmbH, THEIR SUBSIDIARIES AND AFFILIATES DOING BUSINESS IN LOCAL JURISDICTIONS (collectively "SUPPLIERS"), ARE SOLD BY THE RESPECTIVE LEGAL ENTITY OF THE SUPPLIER SUBJECT TO SUPPLIERS' STANDARD CONDITIONS OF SALE, WHICH ARE INCLUDED IN THE APPLICABLE DISTRIBUTOR OR OTHER SALES AGREEMENT, PRINTED ON THE BACK OF ORDER ACKNOWLEDGMENTS AND INVOICES, AND AVAILABLE UPON REQUEST. ALTHOUGH ANY INFORMATION, RECOMMENDATIONS, OR ADVICE CONTAINED HEREIN IS GIVEN IN GOOD FAITH, SUPPLIERS MAKE NO WARRANTY OR GUARANTEE, EXPRESS OR IMPLIED, (i) THAT THE RESULTS DESCRIBED HEREIN WILL BE OBTAINED UNDER END-USE CONDITIONS, OR (ii) AS TO THE EFFECTIVENESS OR SAFETY OF ANY DESIGN INCORPORATING SUPPLIERS' PRODUCTS, MATERIALS, SERVICES, RECOMMENDATIONS OR ADVICE. AFOREMENTIONED EXCLUSIONS OR LIMITATION OF LIABILITY ARE NOT APPLICABLE TO THE EXTENT THAT THE END-USE CONDITIONS AND/OR INCORPORATION CONDITIONS CORRESPOND TO THE RECOMMENDED CONDITIONS OF USE AND/OR OF INCORPORATION AS DESCRIBED BY SUPPLIER IN ITS PRODUCT DATA SHEET AND/OR PRODUCT SPECIFICATIONS. EXCEPT AS PROVIDED IN SUPPLIERS' STANDARD CONDITIONS OF SALE, SUPPLIERS AND THEIR REPRESENTATIVES SHALL IN NO EVENT BE RESPONSIBLE FOR ANY LOSS RESULTING FROM ANY USE OF ITS MATERIALS, PRODUCTS OR SERVICES DESCRIBED HEREIN.

Each user bears full responsibility for making its own determination as to the suitability of Suppliers' materials, services, recommendations, or advice for its own particular use. Each user must identify and perform all tests and analyses necessary to assure that its finished parts incorporating Suppliers' products, materials, or services will be safe and suitable for use under end-use conditions. Nothing in this or any other document, nor any oral recommendation or advice, shall be deemed to alter, vary, supersede, or waive any provision of Suppliers' Standard Conditions of Sale or this Disclaimer, unless any such modification is specifically agreed to in a writing signed by Suppliers. No statement contained herein concerning a possible or suggested use of any material, product, service or design is intended, or should be construed, to grant any license under any patent or other intellectual property right of Suppliers or any of its subsidiaries or affiliates covering such use or design, or as a recommendation for the use of such material, product, service or design in the infringement of any patent or other intellectual property right.

*SilGlaze is a trademark of Momentive Performance Materials Inc.

GE is a registered trademark of General Electric.

Momentive and M-design logo are trademarks of Momentive Performance Materials Inc.

Copyright 2003-2008 Momentive Performance Materials Inc. All rights reserved.