



**IGS3743B 040 5GP (40.0LBS-18.14KG)
Silicone Catalyst - Part B**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Waterford Plant
260 Hudson River Rd
Waterford NY 12188

Revised: 02/25/2009
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Catalyst
Formula: Mixture

HMIS

Flammability: 2 Reactivity: 1 Health: 3

NFPA

Flammability: 2 Reactivity: 1 Health: 3

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

DANGER! CORROSIVE Causes eye burns. Harmful if absorbed through the skin. May cause severe eye irritation. May cause adverse liver, kidney, and CNS effects. May be harmful if swallowed or inhaled. May cause adverse reproductive effects. Adverse reproductive effects reported in animals.

Form: solid Color: black Odor: amine-like

POTENTIAL HEALTH EFFECTS

INGESTION

Liver and kidney injuries may occur. Harmful if swallowed. Causes vomiting, nausea, and diarrhea. Irritation of the mouth, throat, and stomach.

SKIN

Harmful if absorbed through the skin. Skin absorption may cause kidney damage. May cause skin irritation.

INHALATION

Symptoms of overexposure may be headache, dizziness, tiredness, nausea and vomiting. Harmful if inhaled. Causes irritation of the mouth, nose, and throat. May cause damage to nasal and respiratory passages.

EYES

Causes severe eye irritation may damage tissue. May cause permanent eye damage. May cause corneal injury.

MEDICAL CONDITIONS AGGRAVATED

Respiratory disorder Pre-existing liver or kidney disorders. Skin disorders.



IGS3743B 040 5GP (40.0LBS-18.14KG)
Silicone Catalyst - Part B

SUBCHRONIC (TARGET ORGAN)

Respiratory disorder; Dermatitis; Liver and kidney damage.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Inhalation; Dermal; Eyes

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
gamma-Aminopropyltriethoxysilane	919-30-2	10 - 30 %
tetra-n-propyl orthosilicate	682-01-9	10 - 30 %
DIBUTYL TINOXIDE	818-08-6	< 1 %
<u>B. NON-HAZARDOUS</u>		
Polydimethylsiloxane	63148-62-9	30 - 60 %

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. Slowly dilute with 1-2 glasses of water or milk and seek medical attention. Never give anything by mouth to an unconscious person.

SKIN

In case of contact, immediately flush skin with plenty of soap and water for at least 15 minutes. Get medical attention.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, or suspected contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention immediately after flushing.



IGS3743B 040 5GP (40.0LBS-18.14KG)
Silicone Catalyst - Part B

NOTE TO PHYSICIAN

None known.

5. FIRE-FIGHTING MEASURES

FLASH POINT: > 93.3 °C; 200 °F
METHOD: estimated
IGNITION TEMPERATURE: Unknown
FLAMMABLE LIMITS IN AIR - LOWER (%): not applicable
FLAMMABLE LIMITS IN AIR - UPPER (%): not applicable

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE
Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA
Foam, Carbon dioxide (CO₂), Dry chemical

SPECIAL FIRE FIGHTING PROCEDURES
Corrosive material., Wear suitable protective equipment., Positive-pressure self-contained breathing apparatus.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED
Wipe, scrape or soak up in an inert material and put in a container for disposal. Wear proper protective equipment as specified in the protective equipment section. Warn other workers of spill. Increase area ventilation. Person not trained should evacuate area.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Danger! Corrosive. Avoid contact with skin and eyes. Use only in well-ventilated areas. Keep container closed when not in use to prevent contact with acidic, basic or oxidizing materials. Good hygienic practices should be observed. Work clothes should be washed separately at the end of each work day. Disposable clothing should be discarded with material.



**IGS3743B 040 5GP (40.0LBS-18.14KG)
Silicone Catalyst - Part B**

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Use only in well-ventilated areas.; Eyewash stations; Showers; Exhaust ventilation

RESPIRATORY PROTECTION

Use only in well-ventilated areas.

PROTECTIVE GLOVES

Rubber or plastics gloves

EYE AND FACE PROTECTION

Monogoggles

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

<u>Component</u>	<u>CAS RN</u>	<u>Source</u>	<u>Value</u>
------------------	---------------	---------------	--------------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

BOILING POINT - C & F:	not applicable
VAPOR PRESSURE (20 C) (MM HG):	not applicable
VAPOR DENSITY (AIR=1):	No data available
FREEZING POINT:	not applicable
PHYSICAL STATE:	solid
ODOR:	amine-like
COLOR:	black
EVAPORATION RATE (BUTYL ACETATE=1):	Unknown
SPECIFIC GRAVITY (WATER=1):	1.00
DENSITY:	ca. 1.0 g/cm ³
ACID / ALKALINITY (MEQ/G):	not applicable
pH:	not applicable
VOLATILE ORGANIC CONTENT (VOL):	26.5 %(m)
SOLUBILITY IN WATER (20 C):	insoluble
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	partly soluble
VOC EXCL. H2O & EXEMPTS (G/L):	270



IGS3743B 040 5GP (40.0LBS-18.14KG)
Silicone Catalyst - Part B

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO₂); formaldehyde; Amines; Carbon monoxide; Silicon dioxide.; nitrogen oxides (NO_x); Ethanol.; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

Reacts with water forming ethanol. Avoid contact with acids, bases, or oxidizing agents.

CONDITIONS TO AVOID

Keep away from heat and sources of ignition. Keep away from any contact with water.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: Unknown

OTHER

Contains dibutyltin compound(s) - May impair fertility. May cause harm to unborn child.

SKIN IRRITATION

Species: rabbit; Result: Not irritant. Method: OECD-Guideline 404 (Acute Dermal Irritation/Corrosion). Test results are based on analogy with a similar material.

EYE IRRITATION

Eye irritation

MUTAGENICITY

Unknown



**IGS3743B 040 5GP (40.0LBS-18.14KG)
Silicone Catalyst - Part B**

OTHER EFFECTS OF OVEREXPOSURE

Product releases amine vapors during cure.

12. ECOLOGICAL INFORMATION

ECOTOXICITY

No data available

DISTRIBUTION

No data available

CHEMICAL FATE

No data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations., Incineration recommended in approved incinerator according to federal, state, and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Canada DSL Inventory	y (positive listing)
Japan Inventory of Existing & New Chemical Substances (ENCS)	y (positive listing)
Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing Chemical Substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Philippines Inventory of	y (positive listing)



**IGS3743B 040 5GP (40.0LBS-18.14KG)
Silicone Catalyst - Part B**

Chemicals and Chemical
Substances (PICCS)

TSCA list y (positive listing) On TSCA Inventory

EU list of existing chemical substances y (positive listing)

Canada NDSL Inventory n (Negative listing)

For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

CERCLA

PRODUCT COMPOSITION

Chemical

CERCLA Reportable Quantity

SARA (311,312) HAZARD CLASS

Acute Health Hazard

SARA (313) CHEMICALS

CALIFORNIA PROPOSITION 65

This product does not contain any chemicals known to State of California to cause cancer, birth, or any other reproductive defects.

Canadian Regulatory Information

WHMIS HAZARD CLASS

D2B - Toxic Material Causing Other Toxic Effects

D2A - Very Toxic Material Causing Other Toxic Effects

E - Corrosive Material

Other

SCHDLE B/HTSUS: 3815.90 Catalyst Preparation

16. OTHER INFORMATION

OTHER

C = ceiling limit applicable UNKN = unknown determined V = recommended recommended MST = mist parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2)., These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally

NEGL = negligible EST = estimated NE = none established

NF = none found NA = not applicable REC = recommended ND = none determined TS = trade secret R = recommended

STEL = short term exposure limit ppm = parts per million NT = not tested



MOMENTIVE
performance materials

The science behind the solutions.

Material Safety Data Sheet

Version: 2.2
02/25/2009

IGS3743B 040 5GP (40.0LBS-18.14KG) Silicone Catalyst - Part B

applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate.