

# SAFETY DATA SHEET

FOR INDUSTRIAL USE ONLY

SSG4400B 5GP

## Section 1. Product and company identification

**Product name** : SSG4400B 5GP  
**Chemical name** : Not available

**Manufacturer/Importer/  
Distributor Information** : Momentive Amer Seal.  
260 Hudson River Road  
Waterford NY 12188

**Contact person** : 4information@momentive.com

**Telephone** : General information  
+1-800-295-2392

**Emergency telephone number  
Supplier** : CHEMTREC  
1-800-424-9300

## Section 2. Hazards identification

**Classification of the substance or  
mixture** : FLAMMABLE LIQUIDS - Category 4  
SERIOUS EYE DAMAGE/ EYE IRRITATION - Category 1  
SKIN SENSITIZATION - Category 1  
TOXIC TO REPRODUCTION - Category 2  
TOXIC TO REPRODUCTION - Category 2  
SPECIFIC TARGET ORGAN TOXICITY (REPEATED  
EXPOSURE) - Category 1

### GHS label elements

**Hazard pictograms** : 

**Signal word** : Danger

**Hazard statements** : H227 Combustible liquid.  
H318 Causes serious eye damage.  
H317 May cause an allergic skin reaction.  
H361f Suspected of damaging fertility.  
H361d Suspected of damaging the unborn child.  
H372 Causes damage to organs through prolonged or repeated exposure:

### Precautionary statements

**General** : Not applicable.

**Prevention** : Obtain special instructions before use.

Do not handle until all safety precautions have been read and understood.

Use personal protective equipment as required.

Wear protective gloves.

Wear eye or face protection.

Keep away from flames and hot surfaces. - No smoking.

Do not breathe vapor.

Do not eat, drink or smoke when using this product.

Wash hands thoroughly after handling.

Contaminated work clothing should not be allowed out of the workplace.

- Response** : Get medical attention if you feel unwell.  
 IF exposed or concerned:  
 Get medical attention.  
**IF ON SKIN:**  
 Wash with plenty of soap and water.  
 Wash contaminated clothing before reuse.  
 If skin irritation or rash occurs:  
 Get medical attention.  
**IF IN EYES:**  
 Rinse cautiously with water for several minutes.  
 Remove contact lenses, if present and easy to do. Continue rinsing.  
 Immediately call a POISON CENTER or physician.
- Storage** : Store locked up.  
 P403Store in a well-ventilated place.  
 P235Keep cool.
- Disposal** : P501Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Other hazards which do not result in classification** : None known.

### Section 3. Composition/information on ingredients

- Substance/mixture** : Mixture  
**Chemical name** : Not available

Hazardous ingredients	% by weight	CAS number
1-Propanamine, 3-(triethoxysilyl)-	10 - 30	919-30-2
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetrapropyl ester	10 - 30	682-01-9
Stannane, dibutyloxo-	0.1 - 1	818-08-6

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

Occupational exposure limits, if available, are listed in Section 8.

### Section 4. First aid measures

#### Description of necessary first aid measures

- Eye contact** : Get medical attention immediately. Call a poison center or physician. Immediately flush eyes with plenty of water, occasionally lifting the upper and lower eyelids. Check for and remove any

- contact lenses. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician.
- Inhalation** : Get medical attention immediately. Call a poison center or physician. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.
- Skin contact** : Get medical attention immediately. Call a poison center or physician. Wash with plenty of soap and water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing it, or wear gloves. Continue to rinse for at least 10 minutes. Chemical burns must be treated promptly by a physician. In the event of any complaints or symptoms, avoid further exposure. Wash clothing before reuse. Clean shoes thoroughly before reuse.
- Ingestion** : Get medical attention immediately. Call a poison center or physician. Wash out mouth with water. Remove dentures if any. Remove victim to fresh air and keep at rest in a position comfortable for breathing. If material has been swallowed and the exposed person is conscious, give small quantities of water to drink. Stop if the exposed person feels sick as vomiting may be dangerous. Do not induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Chemical burns must be treated promptly by a physician. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and get medical attention immediately. Maintain an open airway. Loosen tight clothing such as a collar, tie, belt or waistband.

#### **Indication of immediate medical attention and special treatment needed, if necessary**

- Notes to physician** : In case of inhalation of decomposition products in a fire, symptoms may be delayed. The exposed person may need to be kept under medical surveillance for 48 hours.
- Specific treatments** : No specific treatment.
- Protection of first aid personnel** : No action shall be taken involving any personal risk or without suitable training. If it is suspected that fumes are still present, the rescuer should wear an appropriate mask or self-contained breathing apparatus. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

See toxicological information (Section 11)

## **Section 5. Fire-fighting measures**

### **Extinguishing media**

- Suitable extinguishing media** : Use dry chemical, CO<sub>2</sub>, water spray (fog) or foam.
- Unsuitable extinguishing media** : Do not use water jet.
- Specific hazards arising from the chemical** : Combustible liquid. In a fire or if heated, a pressure increase will occur and the container may burst, with the risk of a subsequent explosion. Runoff to sewer may create fire or explosion hazard.

**Hazardous thermal decomposition products** : Decomposition products may include the following materials:  
 carbon dioxide  
 carbon monoxide  
 nitrogen oxides  
 metal oxide/oxides  
 Measurements at temperatures above 150°C in presence of air (oxygen) have shown that small amounts of formaldehyde are formed due to oxidative degradation.

**Special protective actions for fire-fighters** : Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Fire water contaminated with this material must be contained and prevented from being discharged to any waterway, sewer or drain.

**Special protective equipment for fire-fighters** : Fire-fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode.

## Section 6. Accidental release measures

### Personal precautions, protective equipment and emergency procedures

**For non-emergency personnel** : No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Shut off all ignition sources. No flares, smoking or flames in hazard area. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

**For emergency responders** : If specialised clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

**Environmental precautions** : Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air).

### Methods and material for containment and cleaning up

**Small spill** : Move containers from spill area. Vacuum or sweep up material and place in a designated, labeled waste container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

**Large spill** : Move containers from spill area. Approach release from upwind. Prevent entry into sewers, water courses, basements or confined areas. Vacuum or sweep up material and place in a designated, labeled waste container. Use spark-proof tools and explosion-proof equipment. Dispose of via a licensed waste disposal contractor. Note: see section 1 of SDS for emergency contact information and section 13 of SDS for waste disposal.

## Section 7. Handling and storage

**Precautions for safe handling**

- Protective measures** : Put on appropriate personal protective equipment (see section 8 of SDS). Persons with a history of skin sensitization problems should not be employed in any process in which this product is used. Avoid exposure - obtain special instructions before use. Avoid exposure during pregnancy. Do not handle until all safety precautions have been read and understood. Do not get in eyes or on skin or clothing. Do not breathe vapor or mist. Do not breathe dust. Do not ingest. Use only with adequate ventilation. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. Use only non-sparking tools. Empty containers retain product residue and can be hazardous.
- Advice on general occupational hygiene** : Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. See also Section 8 for additional information on hygiene measures.
- Conditions for safe storage, including any incompatibilities** : Store in accordance with local regulations. Store in a segregated and approved area. Store in original container protected from direct sunlight in a dry, cool and well-ventilated area, away from incompatible materials (see section 10 of SDS) and food and drink. Store locked up. Eliminate all ignition sources. Separate from oxidizing materials. Keep container tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

**Section 8. Exposure controls/personal protection****Control parameters****Occupational exposure limits**

<b>Ingredient name</b>	<b>Exposure limits</b>
Stannane, dibutyloxo-	<b>NIOSH REL (2005-09-30)</b>  <b>OSHA PEL (1993-06-30) Calculated as Sn</b> Time Weighted Average (TWA) 0.1 mg/m <sup>3</sup> <b>OSHA PEL 1989 Vacated (1989-03-01) Calculated as Sn</b> Time Weighted Average (TWA) 0.1 mg/m <sup>3</sup> Form: Organic <b>ACGIH TLV (1996-05-18) Calculated as Sn</b> Time Weighted Average (TWA) 0.1 mg/m <sup>3</sup> <b>ACGIH TLV (1994-09-01) Calculated as Sn</b> Short Term Exposure Limit (STEL) 0.2 mg/m <sup>3</sup> ()

- Appropriate engineering controls** : Use only with adequate ventilation. If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

The engineering controls also need to keep gas, vapor or dust concentrations below any lower explosive limits. Use explosion-proof ventilation equipment.

- Environmental exposure controls** :
- Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

### Individual protection measures

- Hygiene measures** :
- Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Contaminated work clothing should not be allowed out of the workplace. Wash contaminated clothing before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.
- Eye/face protection** :
- Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists, gases or dusts. If contact is possible, the following protection should be worn, unless the assessment indicates a higher degree of protection: chemical splash goggles and/or face shield. If inhalation hazards exist, a full-face respirator may be required instead.

### Skin protection

- Hand protection** :
- Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary. Considering the parameters specified by the glove manufacturer, check during use that the gloves are still retaining their protective properties. It should be noted that the time to breakthrough for any glove material may be different for different glove manufacturers. In the case of mixtures, consisting of several substances, the protection time of the gloves cannot be accurately estimated.
- Body protection** :
- Personal protective equipment for the body should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Other skin protection** :
- Appropriate footwear and any additional skin protection measures should be selected based on the task being performed and the risks involved and should be approved by a specialist before handling this product.
- Respiratory protection** :
- Use a properly fitted, particulate filter respirator complying with an approved standard if a risk assessment indicates this is necessary. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

## Section 9. Physical and chemical properties

### Appearance

- Physical state** :
- Solid
- Color** :
- Black.
- Odor** :
- Amine-like.
- Odor threshold** :
- Not available
- pH** :
- Not applicable.

<b>Melting point</b>	:	-29.0 °C (20.20- °F)
<b>Boiling point</b>	:	200 °C (392.00 °F)
<b>Flash point</b>	:	Closed cup: 63.0 °C (145.40 °F) (Pensky-Martens.)
<b>Burning time</b>	:	Not available
<b>Burning rate</b>	:	Not available
<b>Evaporation rate</b>	:	< 1
<b>Flammability (solid, gas)</b>	:	Not available
<b>Lower and upper explosive (flammable) limits</b>	:	<b>Lower:</b> Not applicable. <b>Upper:</b> Not applicable.
<b>Vapor pressure</b>	:	Not applicable.
<b>Vapor density</b>	:	Not available
<b>Relative density</b>	:	1.0
<b>Density</b>	:	1 g/cm3
<b>Solubility</b>	:	Hexanes
<b>Solubility in water</b>	:	Reactive
<b>Partition coefficient: n-octanol/water</b>	:	Not available
<b>Auto-ignition temperature</b>	:	Not available
<b>Decomposition temperature</b>	:	Not available
<b>SADT</b>	:	Not available
<b>Viscosity</b>	:	<b>Dynamic:</b> Not available <b>Kinematic:</b> Not available
<b>Volatile organic content</b>	:	22.5 % (w/w) 225 g/l

**Other information**

No additional information.

<b>Section 10. Stability and reactivity</b>
---

<b>Reactivity</b>	:	Stable under normal conditions.
<b>Chemical stability</b>	:	The product is stable.
<b>Possibility of hazardous reactions</b>	:	Under normal conditions of storage and use, hazardous reactions will not occur.
<b>Conditions to avoid</b>	:	Avoid all possible sources of ignition (spark or flame).
<b>Incompatible materials</b>	:	Reactive or incompatible with the following materials: oxidizing materials
<b>Hazardous decomposition products</b>	:	Under normal conditions of storage and use, hazardous decomposition products should not be produced.

<b>Section 11. Toxicological information</b>
--

**Information on toxicological effects**

**Acute toxicity**

Product/ingredient name	Result	Species	Dose	Exposure
1-Propanamine, 3-(triethoxysilyl)-				
	LD50 Oral	Rat	1,570 mg/kg	-
	LD50 Dermal	Rabbit	4,290 mg/kg	-
Stannane, dibutyloxo-				
	LD50 Oral	Rat	45 mg/kg	-

**Conclusion/Summary** : Not determined

**Irritation/Corrosion**

Product/ingredient name	Result	Species	Score	Exposure	Observation
IGS3723B-2011	Skin OECD- Guideline 404 (Acute Dermal Irritation/C orrosion)	Rabbit		4 hrs	-
<b>Remarks:</b> Non-irritant to skin.					
1-Propanamine, 3-(triethoxysilyl)-	eyes - Severe irritant	Rabbit		24 hrs	-
	Skin - Severe irritant	Rabbit		24 hrs	-
	eyes - Mild irritant	Rabbit			-
Stannane, dibutyloxo-	eyes - Severe irritant	Rabbit			-
	Skin - Mild irritant	Rabbit		24 hrs	-

**Conclusion/Summary**

**Skin** : Not determined  
**eyes** : Not determined  
**Respiratory** : Not determined

**Sensitization**

**Conclusion/Summary**

**Skin** : Not determined  
**Respiratory** : Not determined

**Mutagenicity**

**Conclusion/Summary**

: Not determined

**Carcinogenicity**

**Conclusion/Summary**

: Not determined

**Reproductive toxicity**

**Conclusion/Summary**

: Not determined

**Teratogenicity**



**Conclusion/Summary** : Not determined

**Specific target organ toxicity (single exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
Silicic acid (H <sub>4</sub> SiO <sub>4</sub> ), tetrapropyl ester	Category 3		Respiratory tract irritation
Stannane, dibutyl-oxo-	Category 1		thymus

**Specific target organ toxicity (repeated exposure)**

Product/ingredient name	Category	Route of exposure	Target organs
1-Propanamine, 3-(triethoxysilyl)-	Category 1		kidneys

**Aspiration hazard**

Not available

**Information on the likely routes of exposure** : Not available

**Potential acute health effects**

- Eye contact** : Causes serious eye damage.  
**Inhalation** : May give off gas, vapor or dust that is very irritating or corrosive to the respiratory system. Exposure to decomposition products may cause a health hazard. Serious effects may be delayed following exposure.  
**Skin contact** : May cause an allergic skin reaction.  
**Ingestion** : May cause burns to mouth, throat and stomach.

**Symptoms related to the physical, chemical and toxicological characteristics**

- Eye contact** : Adverse symptoms may include the following:  
 pain  
 watering  
 redness  
**Inhalation** : Adverse symptoms may include the following:  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations  
**Skin contact** : Adverse symptoms may include the following:  
 pain or irritation  
 redness  
 blistering may occur  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations  
**Ingestion** : Adverse symptoms may include the following:  
 stomach pains  
 reduced fetal weight  
 increase in fetal deaths  
 skeletal malformations

**Delayed and immediate effects and also chronic effects from short and long term exposure**

**Short term exposure**

- Potential immediate effects** : Not available  
**Potential delayed effects** : Not available

**Long term exposure**

Potential immediate effects : Not available  
 Potential delayed effects : Not available

**Potential chronic health effects**

Conclusion/Summary : Not determined

General : Causes damage to organs through prolonged or repeated exposure: Once sensitized, a severe allergic reaction may occur when subsequently exposed to very low levels.

Carcinogenicity : No known significant effects or critical hazards.  
 Mutagenicity : No known significant effects or critical hazards.  
 Teratogenicity : Suspected of damaging the unborn child.  
 Developmental effects : No known significant effects or critical hazards.  
 Fertility effects : Suspected of damaging fertility.

**Numerical measures of toxicity****Acute toxicity estimates**

<b>Route</b>	<b>ATE value</b>
Oral	10,542.6 mg/kg
<b>Route</b>	<b>ATE value</b>
Dermal	28,807.4 mg/kg

**Section 12. Ecological information****Ecotoxicity**

Product/ingredient name	Result	Species	Exposure
dibutyltin oxide	Acute EC50 0.47 mg/l Fresh water	Aquatic plants - Green algae	72 h

Conclusion/Summary : Not available

**Persistence/degradability**

Conclusion/Summary : Not available

**Bioaccumulative potential**

Product/ingredient name	Species	Exposure	LogPow	BCF	Potential
1-Propanamine, 3-(triethoxysilyl)-			1.7	3.40	low

**Mobility in soil**

Soil/water partition coefficient (KOC) : Not available

Other adverse effects : No known significant effects or critical hazards.

## Section 13. Disposal considerations

- Disposal methods** :
- The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Waste should not be disposed of untreated to the sewer unless fully compliant with the requirements of all authorities with jurisdiction. Waste packaging should be recycled. Incineration or landfill should only be considered when recycling is not feasible. This material and its container must be disposed of in a safe way. Care should be taken when handling emptied containers that have not been cleaned or rinsed out. Empty containers or liners may retain some product residues. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

## Section 14. Transport information

- Special precautions for user** :
- This product must be classified as a Combustible liquid, n.o.s. only when shipped in containers > 450 L (119 gallons) for both import and domestic shipment. Non-bulk containers are classified as shown in the IMDG and IATA classification for both domestic and international shipment.  
Keep away from foodstuffs and animal feed.

## 15.Regulatory information

### United States

- U.S. Federal regulations** :
- United States - TSCA 12(b) - Chemical export notification:** None required.  
**United States - TSCA 5(a)2 - Final significant new use rules:** Not listed  
**United States - TSCA 5(a)2 - Proposed significant new use rules:** Not listed  
**United States - TSCA 5(e) - Substances consent order:** Not listed

### SARA 311/312

- Classification** :
- Fire hazard  
 Immediate (acute) health hazard  
 Delayed (chronic) health hazard

- California Prop. 65:** :
- WARNING: This product contains less than 1% of a chemical known to the State of California to cause birth defects or other reproductive harm.

### Canada

**WHMIS (Canada)** : Class B-3: Combustible liquid with a flash point between 37.8°C (100°F) and 93.3°C (200°F).  
 Class D-2A: Material causing other toxic effects (Very toxic).  
 Class E: Corrosive material

**International regulations**

**International lists** : **Australia inventory (AICS):** All components are listed or exempted.  
**Canada inventory:** All components are listed or exempted.  
**Japan inventory:** All components are listed or exempted.  
**China inventory (IECSC):** All components are listed or exempted.  
**Korea inventory:** All components are listed or exempted.  
**New Zealand Inventory (NZIoC):** All components are listed or exempted.  
**Philippines inventory (PICCS):** All components are listed or exempted.  
**United States inventory (TSCA 8b):** All components are listed or exempted.  
**Taiwan inventory (CSNN):** Not determined.  
**Australia inventory (AICS):** Not determined.  
**Canada inventory:** Not determined.  
**Japan inventory:** Not determined.  
**China inventory (IECSC):** Not determined.  
**Korea inventory:** Not determined.  
**New Zealand Inventory (NZIoC):** Not determined.  
**Philippines inventory (PICCS):** Not determined.  
**United States inventory (TSCA 8b):** Not determined.

**Section 16. Other information**

**Hazardous Material Information System III (U.S.A.) :**

<b>Health</b>	2
<b>Flammability</b>	2
<b>Physical hazards</b>	1

**Caution: HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS® ratings are not required on MSDSs under 29 CFR 1910.1200, the preparer may choose to provide them. HMIS® ratings are to be used with a fully implemented HMIS® program. HMIS® is a registered mark of the National Paint & Coatings Association (NPCA). HMIS® materials may be purchased exclusively from J. J. Keller (800) 327-6868. The customer is responsible for determining the PPE code for this material.**

**Full text of abbreviated H statements** : Not applicable.

**History**

**Date of printing** : 05/19/2015  
**Date of issue/Date of revision** : 04/03/2015  
**Date of previous issue** : 00/00/0000  
**Version** : 1.0  
**Prepared by** : Product Safety Stewardship  
**Key to abbreviations** : ATE = Acute Toxicity Estimate  
 BCF = Bioconcentration Factor  
 GHS = Globally Harmonized System of Classification and Labelling of Chemicals  
 IATA = International Air Transport Association  
 IBC = Intermediate Bulk Container  
 IMDG = International Maritime Dangerous Goods  
 LogPow = logarithm of the octanol/water partition coefficient  
 MARPOL 73/78 = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)  
 RID = The Regulations concerning the International Carriage of Dangerous Goods

**References** : by Rail  
UN = United Nations  
Not available

### **Notice to reader**

Unless otherwise specified in section 1, Momentive Products are intended for industrial application only. They are not intended for specific medical applications, neither for long-lasting (> 30 days) implantation into the human body, injected or directly ingested, nor for the manufacture of multiple usable contraceptives. Keep out of the reach of children.

### **Further Information**

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.